


Product data sheet

LINA45-S 145S-5B1K-30GHM3/840, S
145S-5B1K-30GHM3/840
HALLA




145S-5B1K-30GHM3/840, S Luminaire suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Linear Size: 1683 x 47 x 69 mm Type of installation: Suspended Distribution: Direct-indirect wide-lighting distribution Optics type: Opal diffuser Protection class: I Voltage: 220-240V

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	67.4 W	CRI	80
Total flux	10420 lm	LOR	100%
Luminous efficacy	155 lm/W	Total power	67.4 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	1.5 W	CRI	80
Total flux	290 lm	LOR	100%
Luminous efficacy	193 lm/W	Total power	1.5 W

Mounting mode

Pendant

Shape and measurements

Length: 1.85 in

Width: 66.26 in

Height: 2.72 in

Adjustability

Fixed

Electric

System power: 68.9 W

Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20