

# Product data sheet


TRIANGLE P1300 7600 840 MP  
GLAMOX



IP  
20

TRIANGLE TEXT EN Creating structures TRIANGLE is a luminaire system with unlimited possibilities for the creation of three-dimensional structures thanks to a combination of larger and smaller versions as well as the classic colors of black and white and different mounting heights. Applications To maximize the potential of TRIANGLE it's preferably used in large open areas such as entrances, receptions or other open social areas. Unique look The extruded aluminum profile with an asymmetrically mounted microprismatic or opalized diffuser gives the luminaire a unique look. TRIANGLE can also be surface mounted with brackets.

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 4000 K |
| Nominal lamp power | 82 W    | CRI         | 80     |
| Total flux         | 7600 lm | LOR         | 100%   |
| Luminous efficacy  | 93 lm/W | ULOR        | 84%    |
|                    |         | Total power | 82 W   |

## Mounting mode

Pendant

## Shape and measurements

Length: 44.33 in  
Width: 51.18 in  
Height: 3.15 in

## Adjustability

Height adjustable

## Electric

System power: 82 W

## Protection

IP: 20