



Product data sheet

MONDANA-A
551093.002.76
RZB



Series: Mondana Type of Protection: IP 65 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: plastic, microtextured finish. Diffuser fastening: screw fitting. Diffuser: hand-blown opal glass, satin finish. With Gore-TM Protective Vents membrane valve as standard. Available Colours: pure white (RAL 9010) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 500, H 128 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: AC power, DALI dimmable Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1900lm System power: 21W Beam Angle: 116° Number of fittings B10A: 77 Number of fittings B16A: 124 Number of fittings C10A: 77 Number of fittings C16A: 124 Inrush current: 0,22A Unified Glare Ratio: 18,5 EEC: A+

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 21 W | CRI | 80 |
| Total flux | 1900 lm | LOR | 100% |
| Luminous efficacy | 90 lm/W | ULOR | 14% |
| | | Total power | 21 W |

Mounting mode

Wall mounted

Electric

System power: 21 W

Shape and measurements

Height: 5.04 in
Diameter: 19.69 in

Protection

IP: 65
IK: 03

Adjustability

Fixed

Design

Color of housing: White