

Product data sheet


MIRAGE 3 MRI
 WIDE SEMI-SPEC
 WHITECROFT




IP
44

See lamps to select output and colour variants MIRAGE 3 recessed downlighter semi specular reflector, wide distribution. Narrow 11mm width bezel and shallow depth body. Graphite heat sink for optimum thermal management and superior optics designed for maximum visual comfort. Simple spring ceiling retention method to suit ceiling thicknesses between 5-30mm. Supplied with connected remote driver. Large Round body, 165mm diameter cut out, 173mm over bezel. MRI version for specialist applications such as Healthcare MRI Rooms requiring no ferrous metals or internal electronics. Specialist driver to be ordered seperately. Emergency Output:- 'Emergency lighting to utilise remote central battery'


Light output 1




1 x LED			
Nominal lamp power	25 W	LOR	100%
Lamp flux	2652 lm	Total flux	2652 lm
Luminous efficacy	105 lm/W	Total power	25.3 W
CCT	4000 K		
CRI	90		



1 x LED			
Nominal lamp power	25 W	LOR	100%
Lamp flux	2520 lm	Total flux	2520 lm
Luminous efficacy	100 lm/W	Total power	25.3 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	16 W	LOR	100%
Lamp flux	1796 lm	Total flux	1796 lm
Luminous efficacy	112 lm/W	Total power	16.1 W
CCT	4000 K		
CRI	90		



1 x LED

Nominal lamp power

16 W

Lamp flux

1712 lm

Luminous efficacy

106 lm/W

CCT

3000 K

CRI

90

LOR

100%

Total flux

1712 lm

Total power

16.1 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.94 in

Diameter: 6.69 in

Adjustability

Fixed

Electric

System power: 16.1-25.3 W

Protection

IP: 44