Product data sheet

LUCAS X (1-ARMED BEADED) 9.850.2052.16

LEIPZIGER LEUCHTEN








Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour	r lamp
Nominal lamp power	100 W

Lamp flux

Luminous efficacy 75 lm/W CCT 2000 K CRI 25

LOR 83%
ULOR 2%
Total flux 8621 lm
Total power 115 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in Diameter: 22.44 in Electric

10400 lm

System power: 115 W

Protection

IP: 55