Product data sheet


GENTLESPACE GEN3 BY481X LED350S/840 WB SIA BY480

PHILIPS



Adaptable high-bay lighting offering high efficiency and connectivity options to lighting systems and software applications. With the third generation of the GentleSpace high-bay luminaire, we continue to bring innovations to the market by offering adaptable high bay lighting solutions for high ceiling and industrial applications. GentleSpace gen3 offers a wide variety of options in terms of optics and beam angles (from very narrow to wide), a choice of mounting possibilities and cover materials and a variety of lumen packages. This means that GentleSpace gen3 can easily help you create a tailor-made and ideal lighting solution for almost any high ceiling and/or industrial application. It can also support changes in application requirements (such as layout changes) thanks to its flexible optical system, which can be easily adjusted even after installation. In addition, GentleSpace gen3 also provides the option of advanced connectivity and is ready to be connected to IoT-based system and software applications such as Interact Industry. Overall, whether you are looking for a reliable “fit & forget” solution or one that can be adapted and controlled after installation, GentleSpace gen3 is the ideal solution for your application.

Light output 1



1 x LED

Nominal lamp power	236 W	LOR	100%
Lamp flux	35000 lm	Total flux	34988 lm
Luminous efficacy	148 lm/W	Total power	236 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.62 in
Width: 19.29 in
Height: 3.35 in

Electric

System power: 236 W