

Product data sheet

FLAT POLYMERO XXL
311696.002.1.76
RZB




IP
40

IK
10

Series: Flat Polymero XXL Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base and canopy: metal, lacquered. With steel cable suspension, steplessly adjustable. Diffuser: plastic. Diffuser fastening: sash lock. Available Colours: white Type of Installation: Pendant Dimensions: D 1040, H 230 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 10300lm System power: 100W Beam Angle: 117° Number of fittings B10A: 4 Number of fittings B16A: 6 Number of fittings C10A: 7 Number of fittings C16A: 11 Inrush current: 106A Unified Glare Ratio: 19,5 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	100 W	CRI	80
Total flux	10300 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	10%
		Total power	100 W

Mounting mode

Ceiling mounted

Electric

System power: 100 W

Shape and measurements

Height: 9.06 in
Diameter: 40.94 in

Protection

IP: 40
IK: 10

Adjustability

Fixed