Product data sheet

PASCALA EVO SQUARE
901567.004
RZB



IP 20 IK 03

Series: Pascala EVO Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Bracket: galvanised sheet steel. Inner ring and square cover plate: die cast aluminium. Reflector asymmetrical. Reflector material: MIRO-SILVER with 98 percent total light reflection. Passive cooling. LED included. Connected converter included in separate gearbox. Available Colours: silver, metallic Type of Installation: Recessed ceiling mounting Dimensions: L 242, B 242, H 3 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1250lm System power: 11W Beam Angle: Number of fittings B10A: 14 Number of fittings B16A: 23 Number of fittings C10A: 28 Number of fittings C16A: 46 Inrush current: 16A EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	11 W	CRI	80
Total flux	1250 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	11 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 9.53 in
Width: 9.53 in
Height: 0.04 in

Adjustability

Fixed

Electric

System power: 11 W

Protection

IP: 20
IK: 03