


# Product data sheet

## SPORTS LIGHTING

V1-P0-702X2-04L06-6528040 AIRQUB SPORT TV 280 W 280W 4000K TRANSPARENT 90°

VARTON




IP  
67

IK  
01

High-power floodlight with a wide range of wattage and optics. Best lumens/mass/size ratio in its class of solutions. Material: Cast aluminum radiator, steel body parts, acrylic optic. LEDs with a high color rendering index, for objects with high requirements for television broadcasting. Installation: Surface-mounted using an adjustable bracket. The mounting bracket has an angle of inclination 30° to the horizontal for comfortable aiming of the spotlight. Angle of rotation: 30° to 165° in 5° increment. Application: Outdoor areas. Industrial facilities. Sports lighting. Ingress protection (IP): IP67 Protection class: I Impact resistance: IK01 Power factor: 0,95 Input voltage (AC, 50Hz), V: 90...305 AC frequency, Hz: 50 Input voltage (DC), V: 127...250 Flicker, %: 1 Climatic modification and category of placement: YXЛ1  
<https://www.varton.ru/products/sportivnoe-osveshchenie/airqub-sport-tv/airqub-sport-tv-280-vt/svetodiodnyy-prozhektor-var-ton-airqub-sport-tv-280-vt-4000-k-90/>

### Light output 1



1 x LED			
Nominal lamp power	280 W	LOR	100%
Lamp flux	31000 lm	Total flux	31001 lm
Luminous efficacy	111 lm/W	Total power	280 W
CCT	4000 K		
CRI	90		

### Mounting mode

Ceiling mounted

### Electric

System power: 280 W

### Shape and measurements

Length: 20.63 in

Width: 13.23 in

Height: 15.24 in

### Protection

IP: 67

IK: 01

### Adjustability

Fixed