


Product data sheet

BEAMLINE SLIM
641328.003.2
RZB




IP
20

IK
03

Series: BEAMLINE SLIM Minimalistic recessed ceiling luminaire for aesthetically sophisticated lighting. Housing: metal, powder-coated. Perfect heat management with an aluminium heat sink. LED light unit with MRS technology: Mini-Reflector-System made of metallised thermoplastic with prismatic black glare-suppressing frame for pleasant glare-free light (RUG < 10). Wide beam light distribution. Ceiling installation with spring system. Including separate LED converter with connecting cable 450 mm. Colour: deep black, matt (RAL 9005) Length: 295 mm Width: 45 mm Height: 1.5 mm Cut-out length: 290 mm Cut-out width: 40 mm Recess height: 110 mm Luminaire: recess height: 60 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 90 System power: 25 W Rated luminous flux: 2200 lm Beam angle Down: 46° Luminous efficiency: 88 lm/W Control gear: Regulated power supply Protection class: II Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	25 W	CRI	90
Total flux	2200 lm	LOR	74%
Luminous efficacy	88 lm/W	ULOR	20%
		Total power	25 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 1.77 in
Width: 11.61 in
Height: 0.08 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 25 W

Protection

IP: 20
IK: 03