Product data sheet


CIRKO MONOLYRE
CIRKO MONOLYRE-PC02 45G-48LED-4000K-500 MA
RAGNI



IP 66 IK 08

CIRKO MONOLYRE is an ambiance luminaire with a harmonious design, consisting of a circular body decorated with relief patterns. Placed on a monolyre with curved and twisted arms, it offers both ambient and residential lighting. CIRKO MONOLYRE can be installed in wide range of applications, blending gracefully and discreetly into residential areas, parks, gardens and squares, as well as pedestrian walkways..With an extended lifetime, this IP66 and IK08 luminaire is futureproof through its different variations and offers multiple intelligent management options with its 2 Zhaga sockets above and below. Developed with eco-design in mind, the CIRKO MONOLYRE luminaire is designed to be environmentally friendly, meeting the criteria of energy efficiency, recyclability, sustainability and interoperability.

Light output 1



1 x LED

Nominal lamp power	73.1 W	LOR	100%
Lamp flux	10312 lm	Total flux	10312 lm
Luminous efficacy	141 lm/W	Total power	73.1 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Height: 3.94 in
Diameter: 19.69 in

Adjustability

Fixed

Electric

System power: 73.1 W

Protection

IP: 66
IK: 08