Product data sheet

INMY BOARD 6.1 840
180434
NOKALUX

IP 20 IK 03

Infälld asymmetrisk armatur i My serien mycket lämplig som tavelbelysning. Utförande: Ytter och innerdel i strängsprutad aluminium gavlar av plåt Vit RAL 9016 Bländskydd: Effektiv asymmetrisk linsoptik som ger en jämn ljusspridning. Montage: Armaturen läggs i undertakets T-profil. Fasta längder anpassade för 600 alternativt 1200 modul. Inkoppling: Försedd med 2.5m anslutningsledning med jordad stickpropp. Reglerbar armatur (TDC) är försedd med 5-ledare 2.5m. Båda i halogenfritt utförande. Styrning: Amplitudreglering på variant TDC, tryckknappstyrning, Dali samt inbyggd korridorfunktion även möjlighet till CLO programmering. Driftdon är placerat i armatur. AirC: Sensorsystem med dagsljuskontroll som kan programmeras via app. Sensorn kan även kommunicera trådlöst med flera enheter. I systemet kan även trådlösa strömbrytare integreras. Alternativa utföranden: Alternativa ljusfärger och flöden. CRI 90 Annan armaturfärg. Livslängd L80 Ta25 100 000 h MacAdam 3 SDCM CRI:>80 Energiklass (LED modul): D

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	15.3 W	CRI	84
Total flux	1873 lm	LOR	100%
Luminous efficacy	122 lm/W	Total power	15.3 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 22.09 in
Width: 3.74 in
Height: 2.76 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 15.3 W
Appliance Class: I

Protection

IP: 20
IK: 03