

Product data sheet


ELLK92 LED 400A 2/6 M20M V-CG-S 5700K
12265516111
EATON EMERGENCY LIGHTING



IP
66


• >20 % energy savings compared to similar fluorescent luminaires • Special LED design with direct light distribution • Proved technology. The EVG 09 has been used as a driver for more than 20 years • Various light colour temperatures available - 4000 K / 5700 K • Selected LED chips with perfect binning, low power loss and long life • Ex-e technology for easy maintenance • For ambient temperatures from -25 °C up to +55 °C

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	5700 K
Nominal lamp power	29 W	CRI	80
Total flux	1350 lm	LOR	100%
Luminous efficacy	47 lm/W	ULOR	4%
		Total power	29 W

Light output 2 (integrated)



Lamp type	LED	CCT	5700 K
Nominal lamp power	29 W	CRI	80
Total flux	2700 lm	LOR	100%
Luminous efficacy	93 lm/W	ULOR	4%
		Total power	29 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 29.92 in

Width: 7.40 in

Height: 5.12 in

Adjustability

Fixed

Electric

System power: 58 W

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 66