

# Product data sheet


URBANO LED PLUS VERSION 302W 35100LM 2700K IP66 O61 - FOR RESIDENTIAL AREA ROADS GRAY II TILT ADJUSTME..  
130192.3L46.221

LUG



Professional streetlight luminaire for LED light sources. Mounting: on pillar  $\varnothing 60/76\text{mm}$ , on outriggers  $\varnothing 60/76\text{mm}$  Body: high pressure die-cast aluminum Lateral Surface Wind Exposed:  $0.050\text{ m}^2$  Power supply efficiency  $>93\%$  Power: 220-240V 50/60Hz Lifetime LED (L90): 100 000 h Available on request: DIM 1..10V, LLOC, twilight sensor, 10kV surge protection Additional information: Tilt adjustment:  $5^\circ$ , knife switch (for protection class I), access to the driver chamber without the use of tools, NTC. The possibility of using one or more power supplies in the luminaire. CRI/Ra  $>70$  Additional equipment: additional anti-corrosive protection (index extension: .985) Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: freeways, express roads, local roads, town roads, residential area roads, area lighting, airports, parking areas. Type of optics: O61 - for residential area roads

## Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	302 W	CRI	70
Total flux	35100 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	302 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 35.04 in

Width: 15.35 in

Height: 4.37 in

## Adjustability

Tiltable

## Design

Color of housing: Silver gray

## Electric

System power: 302 W

Controller: DALI

Appliance Class: II

## Protection

IP: 66

IK: 08