


Product data sheet

MOON UNIT 28/54W
547-31545
MOLTO LUCE




Moon Unit, Single pendant lamp, oval shaped polyethylene in white opal; homogeneous, shadow-free light image; Tails brass, pearl chrome plated; height adjustable without tools, transparent supply, 3 x 1mm ²; adapted for new Lumilux SEAMLESS lamp generation 1x T16 28/54W Seamless, 230V, Multiwatt ECG max. Suspension: 3000mm Fixture also available in dimmable versions; IP 20;

Light output 1



1 x Fluorescent lamp tubular T5

Nominal lamp power	54 W	Socket	G5
Lamp flux	4450 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	41%
CCT	3000 K	Total flux	4465 lm
CRI	85	Total power	62 W



1 x Fluorescent lamp tubular T5

Nominal lamp power	28 W	Socket	G5
Lamp flux	2600 lm	LOR	100%
Luminous efficacy	42 lm/W	ULOR	41%
CCT	3000 K	Total flux	2609 lm
CRI	85	Total power	62 W

Mounting mode

Pendant

Shape and measurements

Length: 73.88 in
Width: 7.25 in
Height: 7.09 in

Adjustability

Height adjustable

Electric

System power: 62 W
Appliance Class: I

Protection

IP: 20