Product data sheet

SUPERLINEA SYSTEM 3072 DOWN LED 51.8W RA92 3000K 230V/50HZ IP40 SUPER WIDE FLOOD 100MA
723-73-DP-26-23-Y

EXENIA



IP 40

The new polyspherical or linear fly-eye optics have made it possible to conceive innovative lighting units with absolutely unique size/performance ratios. The Superlinea project aims to make system composition easy and intuitive by offering simple pre-assembled modules, with driver on board, to be connected in sequence with quick couplings and very few additional elements. The configurations offered are divided between: linear modular system in ceiling or suspension mode and simplified stand-alone, ceiling or suspension mode. We have prioritised longitudinal and transverse visual comfort in order to achieve consistently low UGR factors and efficiencies in the region of 140 lumens/W, while maintaining the slim, minimalist design typical of the Exenia style. Each suspended unit is available in single-emission and bi-emission modes

Light output 1



1 x LED

Nominal lamp power	58 W	LOR	100%
Lamp flux	7742 lm	ULOR	100%
Luminous efficacy	133 lm/W	Total flux	7742 lm
CCT	3000 K	Total power	58 W
CRI	92		

Mounting mode

Pendant

Shape and measurements

Length: 0.94 in
Width: 121.10 in
Height: 22.64 in

Adjustability

Fixed

Electric

System power: 58 W

Protection

IP: 40