
Product data sheet


SINUS CURVED SEGMENT DI BLACK PRISM. 90° R920
P33-A49-9005E1840L3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40


low output LED 4000K CRI 90 19,1W 2263lm¹ DALI ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 26,3% https://katalog.planlicht.com/en-gb/search?q=sinus%20segment

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3.18 W	CRI	90
Total flux	377 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	3.18 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3.18 W	CRI	90
Total flux	377 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	3.18 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3.18 W	CRI	90
Total flux	377 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	3.18 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3.18 W	CRI	90
Total flux	377 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	3.18 W

Light output 5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.18 W	CRI	90
Total flux	377 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	3.18 W

Light output 6 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.18 W	CRI	90
Total flux	377 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	3.18 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 37.60 in

Width: 37.60 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 19.1 W

Protection

IP: 40