Product data sheet


ANDHO MINI
722185.0031.1.76
RZB



IP 65 IK 07

Series: ANDHO mini Surface-mounted LED projector in a timeless design. Housing: die-cast aluminium, seawater-resistant powder-coated (C4, in accordance with ISO 12944-6). C5 coating available on request. Integral membrane valve for pressure compensation and avoidance of condensation. MIRO-SILVER reflectors for outstanding efficiency or polycarbonate lenses for the best uniformity of the light cone. Cover clear single-pane toughened glass, edge printed. COB LED with socket for easy replacement. Projector: horizontal rotation range: 360°, vertical swivel range: 90°. Lockable projector orientation. Driver integrated. Colour: anthracite metallic (DB703) Length: 190 mm Width: 114 mm Height: 152 mm Lamp: LED System power: 27 W Rated luminous flux: 3350 lm Luminous efficiency: 124 lm/W Control gear: Converter, dimmable, DALI Protection class: II Type of protection: IP 65

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	27 W	CRI	80
Total flux	3350 lm	LOR	100%
Luminous efficacy	124 lm/W	ULOR	50%
		Total power	27 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Length: 4.49 in
Width: 7.48 in
Height: 5.98 in

Adjustability

Tiltable

Electric

System power: 27 W

Protection

IP: 65
IK: 07