Product data sheet

WEATHERPROOFS & BATTENS - TORNADO EVO 6500K
ATORE6/2/SM3 (70W 6500K)
ANSELL LIGHTING



IP 65

ATORE6/2/SM3 Tornado EVO Supplied c/w Integral Driver • IP65 non-corrosive batten suitable for industrial applications and ancillary areas • High efficiency up to 160 Lm/W • CCT selectable between 4000K, 5000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire • Slim sloped diffuser design creates sleek appearance and offers greater light distribution • LED performance allows point-to-point replacement of existing fluorescent luminaires • Lockable heavy-duty stainless steel clips supplied as standard for added safety and security • Whole luminaire illuminates during emergency operation rather than a small area, allowing less emergency versions required on an installation Operating Temp -20°C to 40°C • Suitable for both internal and external use • 5 Year Product Warranty • IP65

Light output 1



1 x LED

Nominal lamp power	70.1 W	LOR	100%
Lamp flux	9517 lm	Total flux	9516 lm
Luminous efficacy	136 lm/W	Total power	70.1 W
CCT	6500 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 70.87 in
Width: 3.78 in
Height: 3.15 in

Adjustability

Fixed

Design

Designer: Dominic Harkness

Electric

System power: 70.1 W

Protection

IP: 65