

Product data sheet


DALR L40 SQ
DUAL SQ
DEXTRA



IP
20

Dual - 600x600, IP20 Recessed lay-in luminaire, white powder coated steel body, twin high transmission opal diffusers, suitable for lay in installation in exposed "T" ceiling systems. Options: LE3 - Lithium Emergency (418 lumens output) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) H - High Frequency Dimming (Analogue 1-10v) R44 - Reacta 44, Daylight and Presence Detection Sensor RAS - Reacta Air Wireless Presence & daylight RLI - Reacta-Link Wireless Module RLS - Reacta-Link Wireless Presence & Daylight Sensor RC - Reacta-Control Wireless Module RCS - Reacta-Control Wireless, Presence

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	25.9 W	CRI	80
Total flux	3040 lm	LOR	100%
Luminous efficacy	117 lm/W	ULOR	4%
		Total power	25.9 W

Mounting mode

Ceiling recessed

Electric

System power: 25.9 W

Shape and measurements

Length: 23.43 in

Width: 23.43 in

Height: 2.56 in

Protection

IP: 20

Adjustability

Fixed