Product data sheet


QUADRAT
211410.002
RZB



IP 43 IK 02

Series: Quadrat Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 230 V / 50 Hz Base: plastic. Diffuser fastening: spring system. Diffuser: hand-blown opal glass, satin finish. IP43 ceiling mounted, IP44 wall mounted. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 240, B 240, H 110 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 400lm System power: 9W Beam Angle: 135° Unified Glare Ratio: 16,6 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9 W	CRI	80
Total flux	400 lm	LOR	100%
Luminous efficacy	44 lm/W	ULOR	20%
		Total power	9 W

Mounting mode

Wall mounted

Shape and measurements

Length: 9.45 in
Width: 9.45 in
Height: 4.33 in

Adjustability

Fixed

Electric

System power: 9 W

Protection

IP: 43
IK: 02