


Product data sheet

XENA 2 SIDE
55-9946-34-CM
LEDSC4



LedsC4 Xena 2 Side 55-9946-34-CMV2 Bollard for outdoor use. For grazing lighting. Includes 2 cable outlets to facilitate chain mounting. Structure material: Aluminium. Structure finish: Grey. Diffuser material: Polycarbonate. Diffuser finish: Matt. UV protection. Warranty: 5 Years. Product net weight (Kg): 0.87 Product width or diameter (mm): 204 Product height (mm): 48 Class 1. IP: IP66. IK: IK10. LED. No. of lampholders or LEDs: 1. LED brand: CREE. Maximum power of light source: 3W. Colour temperature: 4000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG2. Real flux (lm): 70. Real lm/W: 14. Voltage / frequency range: 100-240/50-60Hz. Voltage: 3. Equipment included: Yes. Multi-voltage equipment included. Total power: 5. Power factor: 0.40. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED			
Nominal lamp power	4.33 W	LOR	100%
Lamp flux	70 lm	ULOR	39%
Luminous efficacy	16 lm/W	Total flux	70 lm
CCT	4000 K	Total power	4.33 W
CRI	75		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 7.87 in
Width: 7.87 in
Height: 1.57 in

Adjustability

Fixed

Electric

System power: 4.33 W
Appliance Class: I

Protection

IP: 66
IK: 10