Product data sheet


URSA LED ALFA 144 2700K DW
2221041/1/DW/10KV
ROSA



IP 66

A luminaire with angular features, made of aluminium - the standard version is anodised in inox or black. Designed to illuminate, among others, highways, expressways, residential streets, pedestrian routes and car parks. Mounted directly on a column with a ⌀ 60 x 95 mm ending. It has a protection class of IP 66 for the optical part and the power input system. The operating temperature range, depending on the power variant, is: from -40°C to +55°C (for 48 W, 60 W, 72 W, 96 W, 120 W), from -40°C to +40°C (for 144 W). The expected service life of the product is L90B10 - 100,000 h. The input voltage frequency is 50/60Hz. Power factor ≥0.95. It is possible to connect the luminaire to an external control system via the DALI interface (optional support for an analogue 1-10V signal).

Light output 1



1 x LED

Nominal lamp power	154 W	LOR	95%
Lamp flux	21400 lm	Total flux	20377 lm
Luminous efficacy	139 lm/W	Total power	154 W
CCT	2700 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 35.04 in
Width: 11.02 in
Height: 5.91 in

Adjustability

Free

Electric

System power: 154 W

Protection

IP: 66