Product data sheet


ARNE I DA LED (OPTIC 038)
9.146.9328.038
LEIPZIGER LEUCHTEN



IP 66

recom. pole height: 4.00m – 7.00m light standards: low and medium lighting requirements lamp: incl. 1 DA+ (2x4) or 1, 2 or 3 DA+ (2x8) LED module(s), easy to replace colour temperature: 4,000K neutral white or 3,000K warm white surge protection: 10kV LED gear: incl. 4DIM driver, up to 100,000 hours; driver with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/DC compatible for operation with central battery systems LED life expectancy: 65,000 hours/ L100/ B10; 100,000 hours/ L90 /B10 for minimum maintenance costs due to an excellent thermal management light control: at extra cost: power reduction, dimming or CLEVER LIGHT optical system: directed light (multi layer) provided by an exchangeable, anti-aging lens technology light distribution: street optics, square optics, area optics, cycle path optics, pedestrian crossing optics luminaire head: die cast aluminium, powder coated colour: DB 703; other colours on request glazing: flat, clear toughened glass glazing wiring: completely wired; via a plug and socket connector within the luminaire head; luminaire head to be hinged upward installation: for top or side entry; ASA 60 or ASA 76 to be ordered separately: • ASA 60 for side entry ø 48mm up to 60mm (0°, -5°, -10°, -15°) or for top entry ø 60mm (0°, 5°, 10°, 15°) • ASA 76 for top entry ø 76mm (0°, 5°, 10°) accessory: adapter ASA, column, pole accessories, wall bracket, cable – to be ordered separately application areas: parks, boulevards, schools, home for elderly people, hotels, factory premises, residential and local distribution roads, main streets, car parks, pedestrian and cycle lanes, holiday parks

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	71 W	CRI	70
Total flux	9844 lm	LOR	68%
Luminous efficacy	139 lm/W	ULOR	34%
		Total power	71 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 22.87 in
Width: 9.37 in
Height: 7.68 in
Weight: 8 kg

Adjustability

Height adjustable

Electric

System power: 71 W

Protection

IP: 66