Product data sheet


ECOLINE OFFICE 1500 WHITE 4710LM 4000K RA>80 ON/OFF

5703821172486



Luminaire suspended/surface-mounted directly in 3000 or 4000 Kelvin LED. Flat design, powder-coated white RAL9010 gloss 25. Double parabolic reflector and diffuser with option of dimmable solution (DALI/SwitchDim). Plug-and-play solution for quick installation. Adjustable wire suspension (2x2 m) ordered as accessory. Light Distribution Direct Light technic LED 35W 4000K Ra>80 SDCM 3 L80/B10 >50.000 hrs Control/Dimming On/Off Protection Class I IP20 Materials and finish Housing: Sheet steel Colour: White (Pure white, 25% gloss) Optics: Double parabolic louvre, satin matt, Aluminium Mounting/Connection Suspended or surface, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 16, B16: 26, C10: 27, C16: 44

Light output 1



1 x LED No

Nominal lamp power	35 W	LOR	100%
Lamp flux	4710 lm	ULOR	21%
Luminous efficacy	135 lm/W	Total flux	4711 lm
CCT	4000 K	Total power	35 W
CRI	80		

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 59.06 in Width: 5.59 in Height: 2.48 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 35 W Appliance Class: I

Protection

IP: 20