


Product data sheet

FASAD ODL04 LED 3000 SH E 20 IP67 840
19.4194.2121.20
LUXIONA



Outdoor luminaire. Assembly: into the ground. The body material is aluminum. Colour - INOX. Dimensions: Ø220 x 300 mm. Weight 4,74 kg. Diffuser: SH (transparent hardened glass). The efficiency of the optical system is 89,97%. Beam angle: (C0-C180) / (C90-C270) - 86° / 86,8°. Light source type: LED. Colour of the light 4000 K. SDCM=2. CRI>80. Lifetime of LED sources: 76000 h L90/B10. Luminaire luminous flux: 3153 lm. Power of luminaire: 28 W. Luminaire's light efficiency: 112,6 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 39 (B10), 62 (B16), 65 (C10), 104 (C16). Operating temperature range: -25 ÷ 30° C. Protection degree: IP67. Impact resistant: IK10. Protection against electric shock: I.

Light output 1



1 x LED			
Nominal lamp power	28 W	LOR	52%
Lamp flux	3505 lm	Total flux	1838 lm
Luminous efficacy	125 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		

Mounting mode

Floor recessed

Shape and measurements

Height: 11.81 in
Diameter: 8.66 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 28 W
Appliance Class: I

Protection

IP: 67
IK: 10

Other operating numbers

Ambient temperature range: -13...86°F