



Product data sheet

PANOS INF Q140LM 22W LED927-65 LDE DB
60813870
ZUMTOBEL



LED ceiling-recessed luminaire, flush-fitting; designed for use where space is limited in ceiling: recess depth only 100mm; "tunable white" LED luminaire, dynamic variation of colour temperature with constant luminaire luminous flux can be controlled via DALI signal (DT8 2010 DALI system); symmetric wide-beam light distribution with maximum luminaire efficiency and optimum photometric properties; lamp(s): 22 W LED927-65; colour-temperature variation: 2700-6500K (warm white – neutral white – daylight white); Luminaire luminous flux: 1012 lm, Luminaire efficacy: 46 lm/W; colour rendering index: RA90; 50,000h service life at 70% luminous flux; includes controllable ballast, dimmable Dali only (separate unit); control only possible via CIRCLE TUNE or LITECOM (DT8 2010); colour temperature and 15-100% illuminance adjustment can be controlled via DALI signal; high-quality reflector unit fastened to modular LED lighting chamber by catch mechanism; high efficiency LED lighting chamber integrated in optimised, passive thermal management system made of extruded aluminium section; lighting chamber and reflector unit appear as one harmonised unit; reflector: smooth reflector in aluminium coated matt finish; reflector made of high quality, UV-resistant polycarbonate; mounting surround made of die-cast aluminium; please order seating surround (planar surround) separately; luminaire unit can be fitted quickly without tools using EASY-CLICK catch; luminaire wired with halogen-free leads; electrical connection: 5-pole terminal; through-wiring not possible; mains voltage: 220-240V / 0/50/60Hz; for use with 220V DC central battery; tool-free quick installation using spring clips in ceilings of thickness 1-25mm; ceiling cutout: 140mm x 140mm, recessed depth: 100mm; weight: 1.01 kg; Note: Please order seating surround (planar surround) separately for installing the luminaire flush with the ceiling (see Accessories)

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	22 W	CRI	90
Total flux	1012 lm	LOR	100%
Luminous efficacy	46 lm/W	Total power	22 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 5.51 in
Width: 5.51 in
Height: 4.02 in
Weight: 1 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 22 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 20
Designation labels: CE