# Product data sheet

164 LED DAMP-PROOF LIGHT FITTING
164 15L120G2 865 KE (16415 0025)
SCHUCH



IP 65 IK 04

LED damp-proof light fitting, 80 W, 12030 lm, 150 lm/W, Class I, IP65, symmetrical wide beam, 6500 K, CRI≥ 80, Ta -20 °C/+40 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Diffuser PMMA satined, Closure Stainless steel (1.4310), Housing Glass fibre reinforced polyester, Colour grey. LED damp-proof light fitting with glass fibre reinforced polyester housing, diffuser, foamed gasket and clips, incl. two safety clips. Powder-coated reflector with highly efficient Zhaga LED modules and ECG with overload and short circuit protection. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 1572,00 mm, Width/Diameter 200,00 mm, Height 98,00 mm, Net weight 3,81 kg.

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 6500 K |
| Nominal lamp power | 80 W | CRI | 80 |
| Total flux | 12030 lm | LOR | 100% |
| Luminous efficacy | 150 lm/W | ULOR | 7% |
| | | Total power | 80 W |

### Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

### Shape and measurements

Length: 61.89 in
Width: 7.87 in
Height: 3.86 in

### Adjustability

Fixed

### Electric

System power: 80 W
Appliance Class: I

### Protection

IP: 65
IK: 04
Designation labels: CE