



# Product data sheet

CALEO SURFACE - A2  
AA20SE-840M-Q530  
LIGHTNET



LED surface-mounted luminaire for walls or ceilings. Direct only light distribution. Luminaire body made of aluminum profile. Surface silver, white, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting. Driver integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial  $\leq$  MacAdam 3. Colour rendering CRI>80 or CRI>90. On request: Integration of emergency lighting components.

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 27 W     | CRI         | 82     |
| Total flux         | 3740 lm  | LOR         | 100%   |
| Luminous efficacy  | 139 lm/W | Total power | 27 W   |

## Mounting mode

Ceiling mounted

## Electric

System power: 27 W

## Shape and measurements

Length: 20.87 in

Width: 20.87 in

Height: 2.95 in

## Protection

## Adjustability

Fixed