


Product data sheet

CIRCULAR DOWNWARD Ø1200 SURFACE
CS4B-00V9AZRU05
LEDSC4



LedsC4 Circular Downward ø1200 Surface CS4B-00V9AZRU05V1 Pendant for indoor use. For downlighting. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 6 Product width or diameter (mm): 1195 Product height (mm): 3000 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 54.5W. Colour temperature: 2700K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 13.5. Photobiological risk: RG1. Real flux (lm): 4261. Real lm/W: 71. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 60. Power factor: 0.90. Dimmable equipment included: 0-10V.

Light output 1



1 x LED			
Nominal lamp power	60 W	LOR	100%
Lamp flux	4261 lm	Total flux	4261 lm
Luminous efficacy	71 lm/W	Total power	60 W
CCT	2700 K		
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 47.24 in
Width: 47.24 in
Height: 1.77 in

Adjustability

Fixed

Electric

System power: 60 W
Appliance Class: I

Protection

IP: 20