


Product data sheet

RONDÒ 3.1 A [3000K 3W 24VDC]
 RD31005AI
 L&L LUCE&LIGHT



Recessed for outdoor applications single beam; drive-over up to 2000 kg; recessed (ground); body in AISI 316L stainless steel, screen in polycarbonate; finishes: anthracite, cor-ten, micro blasted; 1 power LED; 3W - 230Vac, 24Vdc; 230Vac version: built-in power supply unit, 24Vdc version: power supply unit not included; 230Vac version: includes 1,5 m neoprene cable H05RN-F 3x1,0 Ø7 mm, 24Vdc version: includes 1,5 m neoprene cable H05RN-F 2x0,75/0,75 Ø6,3 mm; total delivered lumens: 90 lm (3000K); optics: radial, 10°; LED colour: white - 2700K, 3000K, 4000K; ingress protection: IP67; impact resistance: IK08; equipped with IPS; operating temperature: -10°C +45°C; screen temperature: max 40°C (Ta 25°C); photobiological safety: risk group 1 in accordance with EN62471:2006; 230Vac version: appliance class: I, 24Vdc version: appliance class: III; weight 1,80 kg; dimensions Ø160x87 mm; dimming using a 24Vdc dimmer; accessories: outer casing WC0601, outer casing WC0701, tool for vandal-resistant screws WE0100

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	3 W	CRI	80
Total flux	90 lm	LOR	100%
Luminous efficacy	30 lm/W	ULOR	25%
		Total power	3 W

Mounting mode

Floor recessed

Shape and measurements

Length: 8.91 in

Width: 8.91 in

Height: 1.35 in

Adjustability

Fixed

Electric

System power: 3 W

Appliance Class: III

Protection

IP: 65

IK: 08